








WORKING DIAGRAM

• WORKING AREA WITH IN-SHAPE STABILIZATION







IVECO S-WAY

INFO

OUTRIGGERS HE+HE



WORKING HEIGHT 47,70 m



BASKET HEIGHT 45,70 m



MAX OUTREACH 35,00 m



BASKET LOAD CAPACITY 600 kg



BASKET SIZE **2200/3600x900x1100 mm**



BASKET ROTATION 360°




CONTROLS **Electric**




TURRET ROTATION 700°



GVW **26 ton**





STANDARD ACCESSORIES



- SOCAGE convertible basket possibility (Eternit)
- · 2nd Jib 180 ° manual rotation
- · Possibility of winch on removable JIB
- · Automatic stabilization
- Partially stabilized working areas
- Automatic closing
- Basket control station with console on Socage design including joystick and 7 "LCD display with real-time information
- Intercom with headphones for basket-ground communication
- Main and auxiliary motor start/stop control from the basket
- Multifunction radio remote control for emergency control of the aerial part from the ground and stabilization
- · 2 fixed roto-lamp on the vehicle cabin
- Socket 230V/400V
- Heat exchanger on the hydraulic system
- · 2 folding sides, 2 fixed (h 150 mm)
- 4 plates to stand to the ground
- Anti-corrosion treatment on unpainted components

SAFETY DATA

- · Emergency button
- · Emergency manual hand pump
- · Automatic PTO deactivation
- · Cross-check of open stabilizers
- · Anemometer
- Load limiter in the basket
- Moment limiter with double safety and control of correct operation
- Multi axial device for visual control of frame stabilization
- Emergency descent with electric pump (in the absence of the auxiliary motor)
- Rotation brake of the turret with automatic insertion
- Hydraulic system with differentiated filtering with high efficiency filters both on the delivery lines and on the return lines
- · Multifunction radio control for emergency control
- · Automatism for rotation lock with extension of
- the stabilizers on one side only
- · Chassis flatness sensor
- Flanged block valves

